

SILENT TYPE GENERATOR YX 150

SILENT TYPE GENERATOR YX 150



Kode Produk: YX-150

Cooling System : Closed water-cooledStarting Method : D.C 12V or 24V electric startingRated Voltage (V) : 220/380 or 230/400Rated Frequency (Hz) : 50Rated Speed (Rpm) : 1500

Model	YX 150
Rated Power (KW)	150
Rated Power (KVA)	200

Model	YX 150
Rated Voltage (V)	220/380 or 230/400
Rated Frequency (Hz)	50
Engine Model	6126-42D
Rated Output (KW)	210
Governing Method	electric
Bore x Stroke (mm)	126 x 125
Intake Method	Nature
Oil Volume (L)	64
Fuel Consumption (g/kw.h)	210
Fuel Consumption (L/Hr)	51.3
Oil Consumption (L/Hr)	1.08
Exhaust Flow (L/S)	130
Exhaust Temperature (celsius)	463
Water Volume (L)	25
Cooling System	Closed water-cooled
Starting Method	D.C 12V or 24V electric starting
Alternator Model	274H
Rated Power (kw)	150
Rated Voltage (V)	220/380 or 230/400
Rated Current	284.9
Rated Frequency (Hz)	50
Rated Speed (Rpm)	1500
Power factor Cos	0.8
Phase Connection	3-phase
Winding Connection	4 wires connected (12 wires for 3 phase)
Excitation Method	Brushless
Insulation Class	Class H
Voltage Regulation	Manual / Automatic
Control Panel	
Net Weight - SILENT (kg)	2500
Dimension - SILENT (l x w x h) (m3)	3.65 x 1.3 x 1.85